




## INSERT HEXAGONAL TÊTE RÉDUITE

Type : **IATRH**

Version A-B



Version C-L



### ► *Caractéristiques Techniques*

Dimensions en mm		
M	Epaisseurs à sertir	Ø de perçage -0/+0,1
4 - A	0,5 - 2,0	6,4
4 - B	0,5 - 3,0	6,0
4 - C	0,5 - 2,0	
5 - A	0,5 - 3,0	7,3
5 - B	0,5 - 3,0	
5 - C	0,5 - 2,0	7,0
6 - A	0,7 - 3,0	9,7
6 - B	0,5 - 3,0	
6 - C	0,5 - 3,0	9,0
6 - L	4,0 - 6,0	
8 - A	0,9 - 3,3	10,7
8 - B	0,5 - 3,0	
8 - C	0,7 - 3,0	11,0
8 - L	4,0 - 6,0	
10 - C	1,0 - 3,5	
10 - L	2,0 - 6,0	13

► *Matières* : acier zingué



**SOUDAGE INSTANTANÉ ET  
FIXATIONS INDUSTRIELLES**

22, rue des Celtes - 68510 SIERENTZ

Tél. 03 89 81 59 51 ● Fax : 03 89 81 55 07 ● Courriel : [messages@sifi.fr](mailto:messages@sifi.fr)

[www.sifi.fr](http://www.sifi.fr)