



# INSERTS TARAUDÉS



INSERTS TARAUDÉS

## INSERT CANNELÉ TÊTE FRAISÉE

Type : **IINCTF**



### ► *Caractéristiques Techniques*

			Dimensions en mm	
M	D	f	Epaisseurs à sertir	Ø de perçage -0/+0,1
3 - C 3 - L	7	1	1,3 - 2,0 2,0 - 3,0	5
4 - C 4 - M 4 - L	8	1	1,3 - 2,0 2,0 - 3,0 3,0 - 4,0	6
5 - C 5 - M 5 - L	9	1	1,5 - 2,0 2,0 - 3,0 3,0 - 4,0	7
6 - C 6 - M 6 - L 6 - XL	11	1	1,5 - 3,0 3,0 - 4,0 4,0 - 5,0 5,0 - 6,0	9
8 - C 8 - M 8 - L 8 - XL	14	1,5	1,5 - 3,0 3,0 - 4,0 4,0 - 5,0 5,0 - 6,0	11
10 - C 10 - M 10 - L	16	1,5	1,5 - 3,0 3,0 - 4,5 4,5 - 6,0	13

### ► *Matières* : inox

Existe en version borgne.



Angle de FRAISAGE  
à 90°



**SOUDEGE INSTANTANÉ ET  
FIXATIONS INDUSTRIELLES**

22, rue des Celtes - 68510 SIERENTZ

Tél. 03 89 81 59 51 ● Fax : 03 89 81 55 07 ● Courriel : [messages@sifi.fr](mailto:messages@sifi.fr)

[www.sifi.fr](http://www.sifi.fr)