



# INSERTS TARAUDÉS



INSERTS TARAUDÉS

## INSERT CANNELÉ TÊTE RÉDUITE

Type : **IINCTR**



### ► *Caractéristiques Techniques*



A\* = fût lisse

		Dimensions en mm	
M	D	Epaisseurs à sertir	Ø de perçage -0/+0,1
3 - A*	5,2	0,5 - 1,5	4,7
3 - C	6	0,7 - 1,5	5
3 - M		1,5 - 2,5	
4 - A	6,7	0,5 - 2,0	6,3
4 - C	7	0,7 - 1,5	6
4 - M		1,5 - 2,5	
4 - L		2,5 - 3,5	
5 - A	7,7	0,5 - 2,0	7,3
5 - C	8	0,8 - 2,0	7
5 - M		2,0 - 3,0	
5 - L		3,0 - 4,0	
6 - A	10,2	1,0 - 3,0	9,4
6 - C	10	0,8 - 1,5	9
6 - M		1,5 - 3,0	
6 - L		3,0 - 4,5	
6 - XL		4,5 - 6,0	
8 - A	11,3	1,0 - 3,0	10,5
8 - C	12	0,8 - 1,5	11
8 - M		1,5 - 3,0	
8 - L		3,0 - 4,5	
8 - XL		4,5 - 6,0	
10 - A	14	1,0 - 3,0	14,1
10 - C		0,8 - 1,5	13
10 - M		1,5 - 3,0	
10 - L		3,0 - 4,5	
10 - XL		4,5 - 6,0	



***Matières*** : inox

Existe en version borgne.



**SOUDAGE INSTANTANÉ ET  
FIXATIONS INDUSTRIELLES**

22, rue des Celtes - 68510 SIERENTZ

Tél. 03 89 81 59 51



Fax : 03 89 81 55 07



Courriel : [messages@sifi.fr](mailto:messages@sifi.fr)

[www.sifi.fr](http://www.sifi.fr)