



## GOUJON A SERTIR FILETE

*Type : GS*



### Caractéristiques Techniques

M	e	D ±0,4	P +0,08 / - 0	Longueurs en mm ± 0,4												
				6	8	10	12	15	18	20	22	25	28	30	35	38
2,5	1,0	4,1	2,5	✓	✓	✓	✓	✓	✓	✓	-	-	-	-	-	-
3	1,0	4,6	3,0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
4	1,0	5,9	4,0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
5	1,0	6,5	5,0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
6	1,6	8,2	6,0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
8	2,4	9,6	8,0	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
10	2,4	12,5	10	-	-	-	-	-	-	✓	✓	✓	✓	✓	✓	✓

Dureté maximale de la tôle :

► **Matières :**

- acier zingué .....80 HRB
- inox .....70 HRB
- inox HP .....92 HRB
- aluminium .....50 HRB

► **Légende :**

- ✓ : dimensions courantes
- e : épaisseur minimum de tôle
- P : diamètre de perçage

Pour toutes autres dimensions ou matières, nous consulter.



**SOUDEGE INSTANTANE ET  
FIXATIONS INDUSTRIELLES**

[www.sifi.fr](http://www.sifi.fr)

22, rue des Celtes - 68510 SIERENTZ

Tél. 03 89 81 59 51 ● Fax : 03 89 81 55 07 ● Courriel : [messages@sifi.fr](mailto:messages@sifi.fr)